

CLAIMS

1. A process for reducing content of sulphur compounds and polyaromatic hydrocarbons in a hydrocarbon feed stock having a boiling range between 200°C and 600°C, which process comprises the steps of
- (a) contacting the feed stock with hydrogen over a hydrotreating catalyst at conditions being effective in hydrotreating and obtaining an hydrotreated effluent with the hydrotreated feed stock, hydrogen sulphide and hydrogen,
- (b) cooling the effluent, and
- (c) contacting the effluent with a hydrotreating catalyst at conditions being effective in hydrogenation of polyaromatic hydrocarbons.
2. A process of claim 1, wherein the temperature in step (c) is between 50°C and 150°C lower than outlet temperature from step (a).
3. A process of claim 1, wherein LHSV in step (c) is between 2 and 20 times the LHSV in step (a).
4. A process of claim 1, wherein step (c) is performed in a final catalyst bed of the hydrotreating step.
5. A process of claim 1, wherein the feedstock is characterised by having a 50% boiling point between 300°C and 450°C.

6. A process of claim 1, wherein the hydrotreating catalyst used in step (c) step is a composite of Group VI-B and/or Group VIII metal on a porous refractory inorganic oxide.

5

7. A process of claim 6, wherein the metals are nickel and molybdenum or nickel and tungsten.

8. A process of claim 6, wherein the porous refractory inorganic oxide is alumina or silica-alumina.

10

104210-EEZ89Z60 00768733-012401